

COMSHADE®

Comshade is ideal for large commercial projects where the fabric is supported by engineering certification, that allows the knitted shadecloth to be placed under higher tensile loadings.

Comshade offers excellent weight to strength ratios.

Comshade is heat set, making it much easier to use. It lays very flat so it will not curl or roll up when being marked out, cut and sewn. This means major savings in time and fabrication costs.

Comshade has less shrinkage and is more stable, while maintaining its strength and over 90% UV protection and shade factors.

Comshade comes in an excellent range of 14 fashion colours.



Comshade is made to the highest quality standards, and is supported by a 10 Year UV warranty.

Comshade is made from virgin resins and only the best UV stabilizers from Ciba Speciality Products.

For information and conditions of the warranty, contact your local stockist or visit our web site at www.polyfab.com.au for warranty and maintenance instructions.

Comshade is made to Australian Standards: AS 4174-1994

Technical Specifications

		WARP	WEFT
Breaking Force	N/50mm	799	2147
Breaking Extension	%	83.5	63.0
Tear Resistance (Wing Tear)	N	172	282
Bursting Force (Steel Ball)	Mean N	1861	
Bursting Pressure	Mean kPa	3000	

Colours	UVA %	UVB %	Mean UPF	Shade Factor (Visual Light) %
Porcelain*	95.0	95.4	23	78
Sandstone*	92.8	92.9	14	79
Rust	86.3	86.0	7	74
Bronze	95.8	95.3	21	89
Claret	94.0	95.0	19	88
Yellow	95.3	95.2	21	73
Aquamarine*	90.5	91.3	12	73
Navy Blue	96.3	96.2	27	89
Black	95.9	95.8	24	97
Slate	96.2	96.1	27	94
Blue Gum*	94.3	94.5	18	88
Silver	90.9	90.9	11	95
Light Green	91.8	91.8	13	79
Midnight Green*	95.7	95.5	23	91

Available in:	3.80 x 30m Centre Folded Rolls	3.80 x 50m Straight Rolls	6 x 30m Straight Rolls
	*Colours available		

Average Weight: 330gsm



Distributed by:

Polyfab Australia Pty Ltd
 ABN 54 069 432 846
 4 Joyner Street Moorabbin
 Victoria 3189 Australia
 Tel (03) 9532 3011
 Fax (03) 9532 3488
 © Copyright 2006

POLYFAB
AUSTRALIA

www.polyfab.com.au